



WAVEGUIDE MODEL # CHART UM, UW & UA SERIES

Model # ex. **U M T 28 B S L 2 A 6**

ENVIRONMENT	
M	SHELTERED
W	OUTDOOR
A	AIRBORNE

TTL OPTIONS	
OMIT	NO TTL
T	HIGH LOGIC
V	SINGLE LOGIC
P	POE

SWITCHING OPTIONS	
A	SPDT - 3 PORT
B	DPDT - 4 PORT

VOLTAGE OPTIONS	
8	12 VDC
9	15 VDC
7	24 VDC
2	28 VDC
4	48 VDC

OVERRIDE OPTIONS	
1	SOLDER TERM., no OVRD
2	MICRO-D, no OVRD
6	D-SUB, MALE, no OVRD
7	D-SUB, MALE, w/OVRD
8	CYLINDRICAL CONNECTOR, w/OVRD
9	CYLINDRICAL CONNECTOR, no OVRD

WR SIZE
10
12
15
19
22
28
34
42
51
62
75
90
112

FLANGE OPTIONS	
S	UG COVER
SM	UG COVER, METRIC
O	UG GROOVE
OM	UG GROOVE, METRIC
U	UG CHOKE
UM	UG CHOKE, METRIC
P	CPR FLAT
PM	CPR FLAT, METRIC
Q	CPR GROOVE
QM	CPR GROOVE, METRIC
R	CMR
RM	CMR, METRIC
F	UBR
G	PBR

ELECTRICAL CIRCUIT OPTIONS	
A	NO INDICATORS
OMIT	1 SET INDICATORS

DRIVE OPTIONS	
L	LATCHING
P	PULSE LATCHING
F	FAILSAFE
T	MANUAL
N	LATCHING (+) COM
NP	PULSE LATCHING (+) COM